



## Tailgate Topic - Five Question Quiz

[PP 04/14/2019 - 04/27/2019]

### Pedestrian Safety/Traffic Control [Vision Zero]

1. How many 60-by-60 pads are required on a diversion path that is 600 feet long and only 48 inches wide and why are the pads required?

\_\_\_\_\_

2. Which of the following are recommended for Pedestrians in Work Zones
- a Covered walkways should be provided where pedestrians are exposed to potential injury from falling objects.
  - b Port-a-Potty access
  - c Direct conflicts between pedestrians and vehicular traffic, work vehicles, and other work activities should be avoided.
  - d Advance warning signs and exit information
  - e ADA compliant walkways over construction trenches
  - f Installation/markings for temporary crosswalks
3. Obstacles on the sidewalk or path are only required to be removed if no workers are present?
- \_\_\_\_\_ True      \_\_\_\_\_ False
4. Detour routes should provide?
- a protection from trenches and holes
  - b good sight lines
  - c no mud or dirt
  - d no signs, barriers, materials, vehicles, equipment, or protruding objects that prohibit passage
  - e curb cuts and ramps
5. Temporary curb ramps shall be constructed with;
- a 48 inches wide
  - b Be stable with non-slip surface
  - c Able to support 250 lbs
  - d Have a protective edge to prevent wheelchairs from tipping over
  - e Maximum 8% slope
  - f Maximum 1:12 slope
  - g Require detectable warning when located at pedestrian street crossing

PRINT EMPLOYEE NAME \_\_\_\_\_